

MASON FSN Jack up floor Installation sequence



Set out mount locations

- / Mason supplied engineered layout drawing.
- / Mark mount locations on structural slab.
- / Take note of any clashes with penetrations.



Install Perimeter **Foam** or edge form

- / Supplied by Mason.
- / Install to perimeter and all penetrations.
- / Tape joints.
- / Seal around any penetrations.






Install Bond Breaker

- / Supplied by Mason.
- / Bond breaker installed.
- / Lap and tape joints.
- / Seal any penetrations.
- / No Bondek needed.
- / Structural slab acts as formwork for acoustic slab.

Install FSN Housings to Mason Layout Drawings

- Supplied by Mason.
- Mason project manager inspection point.
- Ensure mounts are laid out in accordance with Mason engineered layout.
- Typically 0.5 man hours/m² to install void former, bond breaker and FSN mounts.



Tie-off Reinforcement

- / Ensure mesh or bar is fixed to support lugs on housing.
- / Reinforcement to Mason or project engineer's details.
- / Mason project manager inspection prior to pour.



.
.
.
.
.
.
.
.


.
.
.
.
.
.
.

Pour Concrete Slab

- / Screed to top of FSN housing.
- / Ensure rubber location plugs are visible.



Jack up Concrete Floor



- / Mason supplied jacking keys.
- / Mason project manager to provide jacking supervision if required.
- / Integrated jacking bolt is turned 2 clockwise turns per pass.
- / Jack slab to documented height (typically 50mm)
- / Typically 4-500m² can be jacked up by a team of 4 men per day. Based on a 50mm airspace.

•
•
•
•
•
•
•
•

Video Overview

[CLICK HERE](#)

A decorative graphic consisting of a 5x5 grid of small red dots in the top-left corner of the slide.

Contact

Mason Mercer

info@masonmercer.com.au

masonmercer.com.au

1800-0-MASON

A decorative graphic consisting of a 4x4 grid of small white dots in the bottom-right corner of the slide.